

# MESSER NRA-M10D - M10 NUT RIVETER ADAPTOR



## Safety Note

Please note the following safety notes to avoid malfunctions, damage or physical injury:

- Please observe all safety notes of the used driving tool (drill)
- Always switch off the driving tool and pull the power plug before maintaining the blind nutting attachment, e.g. changing the nosepieces or when not in use.
- Only use the blind nutting attachment as indicated in this manual for setting blind nuts. The unit is not designed for continuous, professional use.
- Always secure the work piece.
- Do not wear loose clothing or jewellery. Tie up hair or clothing cannot get into moving parts.
- Persons with limited physical, sensorial or mental abilities are not allowed to use the unit, unless they are supervised for their safety by a qualified person or are briefed by the responsible person how to use the unit.
- Only use the blind nutting attachment with the included nosepieces.
- Should the unit become damaged do not use it and have it repaired by a professional or contact our customer support department. Do not disassemble the unit or try repairing it yourself.
- Do not continue using the unit if it was damaged or the unit was dropped down. Please contact our customer support service.

## Technical Data

Model No.	NRA-M10D
Dimensions	Dia.59 x 172mm
Weight	280g
Nosepiece	M4, M5, M6, M8, M10
Capacity	M4, M5, M6, M8, M10
Hex Shank	1/4 (6.35 mm)
Cordless Drill	12V, 14.4V 18V
Cordless Drive	12V, 14.4V 18V
Reversible electric	Drill/Drive
Reversible pneumatic	Drill/Drive
Min. Torque Strength	15 N.M.
Max. rpm	800 rpm

## Overview

1 Hex Shank	1/4 (6.35 mm)
2 Housing	PA+GF
3 Screw	M6 (M4, M5, M8, M10)
4 Sight Window	Blind Nut Loading
5 Nosepiece	M6 (M4, M5, M8, M10)
6 Wrench	1PC

## Assembling and Using

### Before first Use

Remove the unit and the accessory out of the packaging. Keep packaging materials out of reach of children. There is risk of suffocation.

